



Retail



Hospitality



Ticketing



Kiosk



## Market-proven Thermal Receipt Printer

# SRP-350

### HIGHLIGHTS

- Fast printing speed up to 150mm per second
- Easy drop in paper loading
  - Simple paper jam removal
- Various interface cards  
(Serial / Parallel / USB, USB+Serial / Ethernet, Powered USB)
- Small footprint & Ergonomic design
- 2D barcode printing
  - PDF417
  - QR Code
- Value-added options available
  - Melodist with 15 different melodies
  - Splash cover for water resistant
  - SMPS cover for built-in power supply
  - Vertical stand for front exit face up
  - Wall mount bracket for limited space
- User-friendly software tools
  - Virtual Memory Switch Manager (VMSM)
  - NV image download
  - Full version of drivers supported  
Windows Driver, OPOS Driver, JPOS Driver, Linux Cups Driver

*The SRP-350 was developed by Samsung in 2000, and it has been the best seller for more than 10 years across the world, and is continuously loved based on the excellent reliability of the product. Although it is rather an old model, customer satisfaction has been achieved through the update of drivers and firmware to eliminate inconvenience to users, and the product has received good reviews as its modern and solid design is well matched with any POS system.*

### SPECIFICATIONS

#### PRINT

- PRINTING METHOD : Direct thermal
- PRINTING SPEED : 150mm/sec
- RESOLUTION : Standard : 180dpi(7dot/mm)
- CHARACTER SIZE : Font A : 12 X 24 / Font B : 9 X 24  
Korean : 24 X 24 / Chinese : 24 X 24
- CHARACTERS PER LINE :  
Font A : 42 / Font B : 56, Korean : 21 / Chinese : 21
- CHARACTER SET : Alphanumeric Character : 95  
Extended Character : 128 X 34 pages  
International Character : 32
- BARCODES :  
1D : EAN-13, EAN-8, Code 39, Code 93, Code 128, ITF, Coda Bar, UPC-A, UPC-E  
2D : PDF417, QR Code

#### PAPER

- WIDTH : 80mm
- PAPER ROLL DIAMETER : Max Ø 83mm
- PAPER LOADING : Easy Paper Loading

#### RELIABILITY

- PRINTER UNIT : 37 million lines
- TPH : 150 Km
- AUTO CUTTER : 1.8 million cuts

**INTERFACE** : Serial(RS-232C / RS-485) / Parallel (IEEE 1284) / USB / Ethernet

**RECEIVE BUFFER** : 4 Kbytes

**NV IMAGE MEMORY** : 256 Kbytes(Mono)

**USER DEFINE BUFFER** : 12 Kbytes

**EMULATION** : ESC/POS™

**DRIVER** : Windows,OPOS,JPOS,Linux CUPS(Linux kernel 2.4.18 and later)

**SENSOR** : Paper Near End Sensor, Paper End Sensor, Cover Open Sensor

**DRAWER PORT** : 2 ports

**POWER SUPPLY (SMPS)** : AC 100~240V / DC 24V, 2.5A

**DIMENSIONS** : 145 X 195 X 146 (W X L X H mm)

**OPERATING TEMPERATURE** : 0 ~ 45°C

#### OPTION

- SMPS BUILT-IN COVER (RSB-350)
- WALL MOUNT (RWM-350)
- SPLASH PROOF COVER (RSC-350)
- BIXOLON MELODIST (RMB-100)
- VERTICAL STAND (RVS-350)